

5.1 非离子型乳化剂

产品 **Emulsifier EM 15065**

特性 **Emulsifier EM 15065** 是一款基于乙氧基化蓖麻油酯，在不同的工业应用中用作非离子乳化剂。

技术数据	典型数值	规格	
		最小	最大
外观	: 清澈, 液体		visual
颜色	: 棕黄		visual
酸值. (mg KOH/g)	:	7.0	DIN EN ISO 2114
水含量 (wt.%)	:	1.0	DIN 51 777
碱值(mg KOH/g)	:	43.0	53.0 DIN 53 240
皂化值(mg KOH/g)	:	100	120 DIN 51 559-1
密度 20°C (g/ml)	: 1.050		DIN 51 757
折射指数(n_{D20})	: 1.473		DIN 51 423

应用 **EM 15065** 是款非常好的乳化剂，用于稳定和分散水包油的乳化液，最佳剂量取决于配方和应用。

存储 **EM 15065** 出厂时使用原装密闭容器，并且在+ 5°C 至+ 35°C 的室内存储时保质期为 24 个月。

The data contained herein serve as general information for our customers only and are not binding. The data contained herein have been collected to the best of our knowledge and do not constitute any advice or warranty to our customers for any specific application. It is up to our customer at their own risk to determine the suitability of each product for their individual purposes. The products are sold without any representation, warranty or guarantee either expressed or implied. Our liability is limited to the value of the supplied merchandise.