

ADDIMER® 163

产品描述

EINECS: 聚合物

ADDIMER® 163 是一款锌离子离聚物。

物性	单位	目标值
外观	-	米白色粉末
滴点	mg KOH/g	35
粘度 (190°C)	mPa*s	~ 3500

主要应用领域

ADDIMER® 163 在PC、PA、PET、PBT等工程塑料加工中作为内润滑剂、分散剂和成核剂使用。建议添加量为0.3-0.8%。

包装

PE袋 20 kg/包
1吨/托盘

储藏

产品必须在室温下干燥储存。小心阳光和热量。
稳定至少2年，从交付之日起。

危害

本产品不需要按照CLP/GHS指南进行标识。进一步的安全相关数据见安全数据表。

生态学和毒理学特征

该产品是水不溶物。进一步信息见材料安全数据表。

食品法例下的地位

更多详情请洽询。

All information given here are based on our own research or the research of others and believed to be accurate and shall give the user guidance for the application. Nevertheless these data are no specification and due to the versatile possible formulations, applications, processings and further parameters at the formulator/user the usage of this product has to be tested carefully in the particular system/application by the formulator/user. All information mentioned here are not warranted properties. There is no responsibility of the seller if the material is used outside the recommended field of use; any liability, also for any patent infringement, cannot be derived from this.

version 1.0

07.04.2016