

3.1 合成磺酸钠

产品 **Sodium Sulfonate NA 450 F**

特性 **NA 450 F** 是一款不含矿物油的油溶性合成磺酸钠，用酯油进行稀释。在金属加工液中作为分散剂，防锈剂使用，

技术数据	典型 数值	规格 最小	最大	
密度 15°C (g/ml)	: 1.01	0.98	1.02	DIN 51 757
活性成分 (wt.%)	: 62	60		ACL-028
酯油 (wt.%)	: 34	32	36	calculative
水分 (wt.%)	: 3.0		5.0	DIN 51 777-1
无机盐 (wt.%)	: 0.4		0.4	ACL-035
平均分子量	: 435			calculative
闪点 (°C)	: min. 100			DIN EN ISO 2719
色度 (dil. 10%在白油中)	: 4			ACL-014

应用 推荐用于金属加工液，纺织油，清洗剂，防锈剂，涂料，乳化液，矿石浮选，印刷油墨，油漆等产品中。

存储 **NA 450 F** 可以在室内非冷冻的环境下存储至少 12 个月。

The data contained herein serve as general information for our customers only and are not binding. The data contained herein have been collected to the best of our knowledge and do not constitute any advice or warranty to our customers for any specific application. It is up to our customer at their own risk to determine the suitability of each product for their individual purposes. The products are sold without any representation, warranty or guarantee either expressed or implied. Our liability is limited to the value of the supplied merchandise.