

### 3.1 合成磺酸钠

产品 **Sodium Sulfonate NA 420**

特性 **NA 420** 是一款油溶性的合成石油磺酸钠，可以应用于防锈剂，分散剂和乳化剂（防锈性能随分子量增大而增强，而乳化性能随之减弱）。由特殊工艺制成，质量稳定。

技术资料		典型 数值	规格		
			最小	最大	
密度 15°C (g/ml)	:	1.02	1.00	1.04	DIN 51 757
活性成分(wt.%)	:	61	61		ACL-028
矿物油 (wt.%)	:	35	32	36	calculative
水 (wt.%)	:	3.5		5.0	DIN 51 777-1
无机盐 (wt.%)	:	0.4		0.5	ACL-035
平均分子量	:	420			calculative
闪点 (°C)	:	min. 100			DIN EN ISO 2719
色度(dil. 10%白油中)	:	4			ACL-014

应用 推荐应用于金属加工液，纺织油，清洗剂，防锈剂，金属拉拔工艺，乳化剂，油墨，涂料等行业中。

存储 密封保存条件下可以在 0°C 到 40°C 存储至少 12 个月。

The data contained herein serve as general information for our customers only and are not binding. The data contained herein have been collected to the best of our knowledge and do not constitute any advice or warranty to our customers for any specific application. It is up to our customer at their own risk to determine the suitability of each product for their individual purposes. The products are sold without any representation, warranty or guarantee either expressed or implied. Our liability is limited to the value of the supplied merchandise.