

**产品**                    **Kusapour 3055 (PPD)**

**特性**                    **Kusapour 3055** 是一款溶解在中性油中的聚甲基丙烯酸酯的粘性液体，用于润滑基础油的作为降凝剂使用。推荐用于工业润滑油和齿轮润滑油以及单级和多级曲轴箱机油中作为降凝剂。**Kusapour 3055** 在一定的剪切条件下可以有效控制低温粘度。本产品在任何温度和浓度下都完全溶于石油溶剂类。在成品润滑液中，它能与其他常用添加剂相兼容。

技术数据		典型 数值	规格			
			最小	最大		
	外观	:	清晰，粘稠液体			
	颜色	:	淡黄至琥珀			
	粘度 100°C (mm <sup>2</sup> /s)	:	400	200	600	ASTM D445
	密度 25°C (g/cm <sup>3</sup> )	:	0.90	0.88	0.94	ASTM D4052
	闪点 COC (°C)	:		150		ASTM D92
	矿物油含量(wt.%)	:	50			calculative

**应用**                    **Kusapour 3055** 在一类和二类工业油中用作降凝剂。最高混合温度为 90°C

**存储**                    产品可在密封的原始容器中在+5°C 和+45°C 之间安全储存至少保存 2 年

The data contained herein serve as general information for our customers only and are not binding. The data contained herein have been collected to the best of our knowledge and do not constitute any advice or warranty to our customers for any specific application. It is up to our customer at their own risk to determine the suitability of each product for their individual purposes. The products are sold without any representation, warranty or guarantee either expressed or implied. Our liability is limited to the value of the supplied merchandise.