

产品 **Kusacryl 880 (高粘度指数液压油用粘度指数剂)**

特性 **Kusacryl 880** 是一款聚甲基丙烯酸酯类粘度指数改进剂，适用于粘度指数非常高的例如液压油和齿轮油配方中。由于本产品具有非常好的剪切稳定性，低的布氏粘度和良好的降凝特性，因此特别推荐用于需要高粘度的液压油中。该产品已经经过优化，可赋予如降凝，抗乳和耐水硬性等特性

技术资料	典型 数值	规格 最小	最大	
外观	:	清晰粘稠液体		
颜色	:	淡黄至琥珀		
密度 25°C (g/cm ³)	:	0.91	0.88	0.93 ASTM D4052
粘度 100°C (mm ² /s)	:	1400	1100	1900 ASTM D445
闪点°C (COC)	:		150	ASTM D92
SSI(剪切稳定指数) 5% in 150 N base oil 30/250 cycles	:	50		ASTM D3945

应用 在最终产品中推荐的添加量为 1-15%。最高混合温度为 90°C

存储 该产品在正确密封的原始包装中可以在+ 5°C 至+ 40°C 的温度范围内安全地保存至少 12 个月。

The data contained herein serve as general information for our customers only and are not binding. The data contained herein have been collected to the best of our knowledge and do not constitute any advice or warranty to our customers for any specific application. It is up to our customer at their own risk to determine the suitability of each product for their individual purposes. The products are sold without any representation, warranty or guarantee either expressed or implied. Our liability is limited to the value of the supplied merchandise.